ALUMINIUM (STANDARD)

OPERATING TEMPERATURE (°C)

OPERATING PRESSURE (kPa)

MEDIA IN VESSEL

37

30

1" BSPT (STANDARD)

50

30

80

ADDITIONAL INFORMATION:

NOTE:
TEMPERATURE RANGE -10 TO 130°C S.G > 0.8
PRESSURE RANGE 100 TO 1000 kPa gauge
DESIGNED TO OPERATE AT EXTRA LOW VOLTAGE (ELV)
NOT DESIGNED FOR INDUCTIVE OR CAPACITIVE LOADS
LENGTHS >1m SHALL INCUR AN ADDITIONAL FREIGHT CHARGE
ALL WETTED COMPONENTS 316 STAINLESS STEEL

LS-S1-1N-CUSTOM

0

mm
mm

ALUMINIUM (STANDARD)

1" BSPT (STANDARD)

ADDITIONAL INFORMATION:

OPERATING TEMPERATURE (°C)

OPERATING PRESSURE (kPa)

MEDIA IN VESSEL

COMMON WIRING (STANDARD)

37

30

30

30

NOTE:
MINIMUM FLOAT SEPERATION = 55mm BETWEEN CENTRES
= 45mm WITH SINGLE COLLAR
TEMPERATURE RANGE -10 TO 130°C S.G > 0.8
PRESSURE RANGE 100 TO 1000 kPa gauge
DESIGNED TO OPERATE AT EXTRA LOW VOLTAGE (ELV)
NOT DESIGNED FOR INDUCTIVE OR CAPACITIVE LOADS
LENGTHS >1m SHALL INCUR AN ADDITIONAL FREIGHT CHARGE
ALL WETTED COMPONENTS 316 STAINLESS STEEL

LS-S1-2N-CUSTOM

ALUMINIUM (STANDARD)

OPERATING TEMPERATURE (°C)

OPERATING PRESSURE (kPa)

MEDIA IN VESSEL

COMMON WIRING (STANDARD)

37

30

1" BSPT (STANDARD)

30

30

ADDITIONAL INFORMATION:

NOTE:
MINIMUM FLOAT SEPERATION = 55mm BETWEEN CENTRES
= 45mm WITH SINGLE COLLAR
TEMPERATURE RANGE -10 TO 130°C S.G > 0.8
PRESSURE RANGE 100 TO 1000 kPa gauge
DESIGNED TO OPERATE AT EXTRA LOW VOLTAGE (ELV)
NOT DESIGNED FOR INDUCTIVE OR CAPACITIVE LOADS
LENGTHS >1m SHALL INCUR AN ADDITIONAL FREIGHT CHARGE
ALL WETTED COMPONENTS 316 STAINLESS STEEL

LS-S1-3N-CUSTOM

ALUMINIUM (STANDARD)

OPERATING TEMPERATURE (°C)

OPERATING PRESSURE (kPa)

MEDIA IN VESSEL

COMMON WIRING

37

30

1" BSPT (STANDARD)

30

30

ADDITIONAL INFORMATION:

NOTE:
MINIMUM FLOAT SEPERATION = 55mm BETWEEN CENTRES
= 45mm WITH SINGLE COLLAR
TEMPERATURE RANGE -10 TO 130°C S.G > 0.8
PRESSURE RANGE 100 TO 1000 kPa gauge
DESIGNED TO OPERATE AT EXTRA LOW VOLTAGE (ELV)
NOT DESIGNED FOR INDUCTIVE OR CAPACITIVE LOADS
LENGTHS >1m SHALL INCUR AN ADDITIONAL FREIGHT CHARGE
ALL WETTED COMPONENTS 316 STAINLESS STEEL

LS-S1-4N-CUSTOM

ALUMINIUM (STANDARD)

OPERATING TEMPERATURE (°C)

OPERATING PRESSURE (kPa)

MEDIA IN VESSEL

COMMON WIRING

37

30

1" BSPT (STANDARD)

30

30

ADDITIONAL INFORMATION:

NOTE:
MINIMUM FLOAT SEPERATION = 55mm BETWEEN CENTRES
= 45mm WITH SINGLE COLLAR
TEMPERATURE RANGE -10 TO 130°C S.G > 0.8
PRESSURE RANGE 100 TO 1000 kPa gauge
DESIGNED TO OPERATE AT EXTRA LOW VOLTAGE (ELV)
NOT DESIGNED FOR INDUCTIVE OR CAPACITIVE LOADS
LENGTHS >1m SHALL INCUR AN ADDITIONAL FREIGHT CHARGE
ALL WETTED COMPONENTS 316 STAINLESS STEEL

LS-S1-5N-CUSTOM